

JOB _____ ITEM # _____ QTY # _____



750-1



750



R-470
Shown with
optional rotating
bumpers.

SPECIFICATIONS

Models 750 and 750-1 cup or glass rack dollies for 20" x 20" rack size.

PLATFORM

The platform is constructed of 14 ga. stainless steel turned up 1-1/4" on all four sides. On Model 750-1 a 1" O.D. 16 ga. tubular "U" shaped stainless steel handle is welded to the platform corners. The platform has a 1/2" hole in the center to permit drainage when the dolly is washed.

CASTERS

The units are mounted on four 4" diameter heavy duty casters.

MODEL 750: Unit with platform only.

MODEL 750-1: Unit with platform and tubular handle.

OPTIONS

- B - Corner bumper
- PB - Perimeter bumper (Available for 750 only)
- WB - Wheel brakes (set of 2)
- Y4 - Polyurethane 4" casters, set of 4, with ball bearing seals
- Y5 - Polyurethane 5" casters, set of 4, with ball bearing seals

NOTE: Other size platforms are available.

CAPACITY

- ◆ One stack of 20" x 20" racks.

OVERALL DIMENSIONS:

- ◆ Model 750: 20-1/2" long, 20-1/2" wide, 6-1/2" high.
- ◆ Model 750-1: 20-1/2" long, 20-1/2" wide, 36" high.
- ◆ Approximate shipping weight: 30

LIMITED WARRANTY: PIPER PRODUCTS warrants to the original purchaser parts and labor for a period of twelve (12) months from the date of purchase. See manufacturer's complete warranty for details.

It is our policy to build equipment which is design certified by companies that have been accredited at the Federal Level by the Occupational Safety and Health Agency (OSHA) and ANSI as a National Recognized Testing Laboratory. These companies include CSA International, Underwriters Laboratories, and the National Sanitation Foundation. However, a continuing program of product improvement makes it necessary to submit new models to the agencies as they are developed. Consequently, all models may not bear the appropriate labels at all times.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Information is not for design purposes.

MODEL NUMBER

- 750
- 750-1
- R-470

SPECIFICATIONS

Model R-470 cup or glass rack cart for 20" x 20" rack size.

FRAME

The frame is constructed of 1" O.D. 16 ga. stainless steel tubing with 3/4" O.D. integrally welded cross rails for rigidity.

SHELVES AND SLIDES

The unit contains two solid 18 ga. stainless steel shelves, formed with three sides turned up 1" and the front edge turned down 1", and with all edges hemmed. All corners are notched to the contour of, and welded to the frame to form a unitized assembly. One pair of 1" x 2" 16 ga. stainless steel angle slides are welded to the frame between the two shelves. The bottom shelf is 12" above the floor, the angle slides are 6-1/2" above the bottom shelf and the top shelf is 26-1/2" above the floor.

CASTERS

The unit is mounted on four 4" diameter heavy duty casters.

OPTIONS

- R - Rotating bumper
- WB - Wheel brakes (set of 2)
- Y4 - Polyurethane 4" casters, set of 4, with ball bearing seals
- Y5 - Polyurethane 5" casters, set of 4, with ball bearing seals

CAPACITY

- ◆ Five 20" x 20" cup or glass racks.

OVERALL DIMENSIONS

- ◆ 24" long, 23" wide, 36" high.
- ◆ NOTE: Add 3" to length and width for rotating bumpers. Add 2" to length and width for circular bumpers.
- ◆ Shipping weight: 60

SPEC H-3-C

PIPER PRODUCTS
BUILT TO LAST
www.piperonline.net

300 S. 84th Avenue
Wausau, WI 54401
Phone: 800-544-3057
Fax: 715-842-3125