

JOB _____ ITEM # _____ QTY # _____

MODEL NUMBER

GSM 4

UNIT COMPARISONS

	GSM 4	GSM 5 Star	XL, XL Star, & MultiCut-240
HP	1/2	1/2	1
RPMs	340	340	280
Upper Housing	Cast Aluminum	Stainless Steel	Cast Aluminum
Blades Available	47	52	42,44,42
Antimicrobial Protection Pusher		✓	✓
Antimicrobial Protection Blades	✓	✓	

DIMENSIONS

- ◆ Foot Print = 9.29" x 9.8"
- ◆ Overall Depth = 12.40"
- ◆ Overall Width = 10.75"
- ◆ Overall Height = 21.26"
- ◆ Kidney Shaped Hopper = 2.4" x 5.2"
- ◆ Continuous Feed Hopper = 2.05" diameter
- ◆ Freight Class: 85
- ◆ Net Weight: 36.38 lbs.
- ◆ Shipping Weight: 43.65 lbs.
- ◆ Shipping Dimensions: 29.92"L x 14.57"W x 16.93"H

CORD AND PLUG

Attached six-foot flexible 3-wire cord and plug fits a grounded receptacle.

CONSTRUCTION

The housing, removable hinged hopper head, food hoppers, removable food pusher and ejector plate are made of polished cast aluminum.

There are 47 cutting discs available. The discs are antimicrobial durable composite fiberglass. The knives are hardened, ground, leathered and hand-polished to a razor sharp edge for precision cutting and long life.

WARRANTY

Two years parts and labor.



GSM 4



STANDARD FEATURES

- ◆ Kidney shaped material pusher is made from mold cast food grade aluminum
- ◆ Powerful 1/2 HP gear-driven motor
- ◆ Optimum plate speed of 336 RPMs
- ◆ Polished food grade cast aluminum construction & sealed upper housing
- ◆ Double safety interlock - hopper head and food pusher
- ◆ Ergonomic 45° food hopper incline
- ◆ Removable hopper head and food pusher (no tools required)
- ◆ Discs are antimicrobial durable composite fiberglass & dishwasher safe
- ◆ Stainless steel knives are hardened, ground, leathered and hand-polished
- ◆ 47 discs are available

CAPACITY

Processes up to 600 lbs. per hour. Ideal for up to 300-400 meals.

MOTOR

1/2 HP, 115V-60HZ-1 Phase, 3 amps, automatic reset thermal overload protection.

ON/OFF LATCH (INTERLOCKS)

The hopper latch serves as the on/off switch and interlock for the hopper head. The unit will not operate with the hopper head open or unlatched.

GEAR DRIVE

Sealed planetary gear transmission with permanent grease lubrication. Output 336 RPMs.

DESIGN

Ergonomic 45° incline for convenient feeding, cutting and ejection of food. Separate food hopper permits continuous cutting of long products. The food pusher enables even pressure to be applied when cutting food. The hopper head, food pusher and cutting discs are easily removable, without the use of tools, for quick cleaning.

SPEC T-1

PIPER PRODUCTS
BUILT TO LAST
www.piperonline.net

300 S. 84th Avenue
 Wausau, WI 54401
 Phone: 800-544-3057
 Fax: 715-842-3125



F1

	Slicing	inches	mm
<input type="checkbox"/>	F1-5	1/32	1
<input type="checkbox"/>	F2-5	5/64	2
<input type="checkbox"/>	G3-5	1/8	3
<input type="checkbox"/>	G4-5	5/32	4
<input type="checkbox"/>	G6-5	15/64	6
<input type="checkbox"/>	G8-5	5/16	8
<input type="checkbox"/>	G10-5	3/8	10
<input type="checkbox"/>	G12-5	15/32	12
<input type="checkbox"/>	SU5-5*	3/16	5
<input type="checkbox"/>	SU7-5*	9/32	7
<input type="checkbox"/>	TO-5	3/16	5



S2

	Julienne	inches	mm
<input type="checkbox"/>	S1.5-5	1/16	1.5
<input type="checkbox"/>	S2-5	5/64	2
<input type="checkbox"/>	S3-5	1/8 x 5/64	3 x 2
<input type="checkbox"/>	PA4K-5	5/32	4
<input type="checkbox"/>	PA5K-5	3/16 x 5/32 5 x 4	5



G3



PA4

	French Fry	inches	mm
<input type="checkbox"/>	BT6-5	15/64	6
<input type="checkbox"/>	BT7-5	9/32	7
<input type="checkbox"/>	BT8-5	5/16	8
<input type="checkbox"/>	BT10-5	3/8	10

*(SU discs are wavy slices)



0

	Shredding	inches	mm
<input type="checkbox"/>	11-5	5/64	2
<input type="checkbox"/>	9-5	3/32	2.5
<input type="checkbox"/>	7-5	1/8	3
<input type="checkbox"/>	4-5	5/32	4
<input type="checkbox"/>	3-5	3/16	5
<input type="checkbox"/>	1-5	9/32	7
<input type="checkbox"/>	0-5	23/64	9
<input type="checkbox"/>	00-5	7/16	11
<input type="checkbox"/>	23-5	3/32	2.5



BT7

	Dicing	inches	mm
<input type="checkbox"/>	W6-5	1/4 x 1/4 x 5/16	6 x 6 x 8
<input type="checkbox"/>	W8-5	5/16	8
<input type="checkbox"/>	W10-5	3/8	10
<input type="checkbox"/>	W14-5	9/16	14
<input type="checkbox"/>	W20-5 *	25/64 x 25/64 x 25/64	20 x 20 x 20



23

	Shaving	inches	mm
<input type="checkbox"/>	HS-5	1/64	.5



W6

*Soft Only Products



HS

	Grating	
<input type="checkbox"/>	14-5	fine cut (parmesan and romano cheese powder)



SM

	Sickle Disc	inches	mm
<input type="checkbox"/>	SM1.5-5	1/16	1.5
<input type="checkbox"/>	SM2.5-5	3/32	2.5
<input type="checkbox"/>	SM3.5-5	9/94	3.5
<input type="checkbox"/>	SM4.5-5	11/64	4.5
<input type="checkbox"/>	SM5.5-5	7/32	5.5
<input type="checkbox"/>	SM6.5-5	1/4	6.5



SCV-1



SCH-3



WR-3

	Option	Description
<input type="checkbox"/>	SCV-1	Vertical disc storage case (1 disc) *Will not hold cubing or dicing discs
<input type="checkbox"/>	SCH-3	Horizontal disc storage case (3 discs)
<input type="checkbox"/>	SCH-4	Horizontal disc storage case (4 discs)
<input type="checkbox"/>	SCV-7/3	Vertical disc storage rack (3 discs)
<input type="checkbox"/>	WR3	Three peg wall rack

T-1 SPEC

PIPER PRODUCTS
BUILT TO LAST
www.piperonline.net

300 S. 84th Avenue
Wausau, WI 54401
Phone: 800-544-3057
Fax: 715-842-3125

LIMITED WARRANTY: PIPER PRODUCTS warrants to the original purchaser parts and labor for a period of twelve (12) months from the date of purchase. See manufacturer's complete warranty for details.

It is our policy to build equipment which is design certified by companies that have been accredited at the Federal Level by the Occupational Safety and Health Agency (OSHA) and ANSI as a National Recognized Testing Laboratory. These companies include CSA International, Underwriters Laboratories, and the National Sanitation Foundation. However, a continuing program of product improvement makes it necessary to submit new models to the agencies as they are developed. Consequently, all models may not bear the appropriate labels at all times.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Information is not for design purposes.